



| REVISION HISTORY |      |      |             |      |        |
|------------------|------|------|-------------|------|--------|
| ECO              | ZONE | REV. | DESCRIPTION | DATE | APPR'D |
|                  |      |      |             |      |        |



| MINIMUM GAP TO CEILING |     |     |
|------------------------|-----|-----|
| CONDITION              | "A" |     |
| SERVICE MODE           | 38  | 1.5 |
| TOOL ACCESS            | 165 | 6.5 |
| PANEL REMOVAL ONLY     | 32  | 1.3 |
| MINIMUM GAP            | 17  | 0.7 |

STANDARD PANEL DIMENSIONS  
[47.71]  
1211.8

ERO PANEL DIMENSIONS  
[47.73]  
1212.5


STANDARD PANEL DIMENSIONS  
[26.87]  
682.6

ERO PANEL DIMENSIONS  
[26.90]  
683.3

**WITHOUT MOUNT**  
STANDARD PANEL SHOWN



**WITH MOUNT**  
ERO PANEL SHOWN

**SERVICE MODE**



"A" SEE TABLE

DUE TO HOT AIR BUILD UP AT THE TOP OF AN INSTALLED ARRAY, PLANS SHOULD BE MADE TO ALLOW THIS AIR TO ESCAPE EITHER OUT THE FRONT, BACK OR CEILING WHERE SHOWN.



**SIDE VIEWS**



**FRONT VIEW**  
STANDARD PANEL SHOWN

**BOTTOM VIEW**


- PANEL TEMPERATURES CAN INCREASE 3-5° WITH EACH VERTICALLY STACKED UNIT.
  - SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE
- NOTES: UNLESS OTHERWISE SPECIFIED.

|   |         |              |         |                             |  |
|---|---------|--------------|---------|-----------------------------|--|
| UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN MILLIMETERS (INCHES) |         | ENGR BY      | 29DEC15 |                             | PLANAR SYSTEMS, INC.<br>1195 NW COMPTON DRIVE<br>BEAVERTON, OR 97006 USA |
| TOLERANCES:   |         | DRAWN BY     | MAZ     |                             |  |
| X= ±1   | XX= ±25 | CHECKED BY   |         | TITLE                       |  |
| .X= ±.5   | ∠= ±1°  | USED ON      |         | CLARITY MATRIX MX/LX55HDX-L |  |
| DIMENSIONING AND TOLERANCING PER ASME Y14.5M-1994                 |         | MATERIAL     |         | PRODUCT OUTLINE             |  |
| THIRD ANGLE PROJECTION  |         | FINISH       |         | SIZE                        | REV  |
|   |         |              |         | D                           | A  |
| SCALE   | 1:5     | DO NOT SCALE | SHEET   | 1 OF 8                      |  |

THIS DRAWING CONTAINS INFORMATION PROPRIETARY TO PLANAR SYSTEMS, INC. ANY REPRODUCTION IN PART OR WHOLE WITHOUT THE WRITTEN PERMISSION OF PLANAR SYSTEMS IS PROHIBITED. THIS DRAWING IS SUPPLIED FOR INFORMATION, IDENTIFICATION, ENGINEERING, EVALUATION, AND/OR INSPECTION PURPOSES ONLY AND MAY NOT BE USED AS BASIS FOR THE MANUFACTURING OF PRODUCTS OR THE FURNISHING OF SERVICES TO PLANAR SYSTEMS OR TO ANY THIRD PARTY UNLESS AUTHORIZED IN WRITING BY PLANAR SYSTEMS.



**OPTIONAL LANDSCAPE WALL STUD ADAPTER BRACKET**  
2 PER LCD MOUNT, ATTACHMENT ORIENTATION SHOWN



5.

| ROWS | COLUMNS | WALL DIMENSIONS (mm/in) |        |          |        |        |        |
|------|---------|-------------------------|--------|----------|--------|--------|--------|
|      |         | HEIGHT                  | WIDTH  | DIAGONAL |        |        |        |
| 2    | 2       | 1367.6                  | 53.84  | 2426.0   | 95.51  | 2784.9 | 109.64 |
| 2    | 3       | 1367.6                  | 53.84  | 3640.2   | 143.31 | 3888.6 | 153.09 |
| 3    | 3       | 2052.6                  | 80.81  | 3640.2   | 143.31 | 4179.0 | 164.53 |
| 3    | 4       | 2052.6                  | 80.81  | 4854.3   | 191.12 | 5270.4 | 207.50 |
| 4    | 4       | 2737.5                  | 107.78 | 4854.3   | 191.12 | 5573.0 | 219.41 |
| 5    | 5       | 3422.5                  | 134.74 | 6068.5   | 238.92 | 6967.1 | 274.29 |

4. IT IS RECOMMENDED THAT FOR FLUSH MOUNT WALLS, A MINIMUM OF 13mm (0.5") GAP BE LEFT AT THE SIDES AND A MINIMUM OF 25mm (1.0") GAP BE LEFT AT THE BOTTOM. SEE PAGE ONE FOR TOP GAP RECOMMENDATIONS


3. IT IS RECOMMENDED THAT A MINIMUM OF 5 FEET OF CABLE IS AVAILABLE FOR PANELS NEXT TO THE CONDUIT OPENING. MORE WILL BE NEEDED FOR PANELS FARTHER AWAY.

2. ENSURE THE LCD MOUNTS ARE MOUNTED FLAT, LEVEL, AND PLUMB.

1. SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE

NOTES: UNLESS OTHERWISE SPECIFIED.

|   |          |            |         |               |  |
|---|----------|------------|---------|---------------|--|
| UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN MILLIMETERS (INCHES)  |          | ENGR BY    | 29DEC15 | <b>PLANAR</b> | PLANAR SYSTEMS, INC.<br>1195 NW COMPTON DRIVE<br>BEAVERTON, OR 97008 USA |
| TOLERANCES:   |          | DRAWN BY   | MAZ     |               |  |
| X= ±1   | XX= ±.25 | CHECKED BY |         | TITLE         | CLARITY MATRIX MX/LX55HDX-L MOUNT BRACKET LAYOUT                         |
| X= ±.5  | ∠= ±1°   | USED ON    |         | SIZE          | D  |
| DIMENSIONING AND TOLERANCING PER ASME Y14.5M-1994   |          | MATERIAL   |         | PART NO.      | -  |
| THIRD ANGLE PROJECTION  |          | FINISH     |         | DRAWING NO.   | HX2 55L Outline  |
| THIS DRAWING CONTAINS INFORMATION PROPRIETARY TO PLANAR SYSTEMS, INC. ANY REPRODUCTION IN PART OR WHOLE WITHOUT THE WRITTEN PERMISSION OF PLANAR SYSTEMS IS PROHIBITED. THIS DRAWING IS SUPPLIED FOR INFORMATION, IDENTIFICATION, ENGINEERING, EVALUATION, AND/OR INSPECTION PURPOSES ONLY AND MAY NOT BE USED AS BASIS FOR THE MANUFACTURING OF PRODUCTS OR THE FURNISHING OF SERVICES TO PLANAR SYSTEMS OR TO ANY THIRD PARTY UNLESS AUTHORIZED IN WRITING BY PLANAR SYSTEMS. |          | SCALE      | 1:5     | DO NOT SCALE  | SHEET 2 OF 8   |




RECOMMENDED LOCATION FOR CABLE INGRESS BETWEEN PANEL COLUMNS

DISPLAY OUTLINE

4. IT IS RECOMMENDED THAT FOR FLUSH MOUNT WALLS, A MINIMUM OF 13mm (0.5") GAP BE LEFT AT THE SIDES AND A MINIMUM OF 25mm (1.0") GAP BE LEFT AT THE BOTTOM. SEE PAGE ONE FOR TOP GAP RECOMMENDATIONS
3. IT IS RECOMMENDED THAT A MINIMUM OF 5 FEET OF CABLE IS AVAILABLE FOR PANELS NEXT TO THE CONDUIT OPENING. MORE WILL BE NEEDED FOR PANELS FARTHER AWAY.
2. ENSURE THE LCD MOUNTS ARE MOUNTED FLAT, LEVEL, AND PLUMB.
1. SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE

NOTES: UNLESS OTHERWISE SPECIFIED.

|  |          |   |              |
|--|----------|---|--------------|
| UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN MILLIMETERS (INCHES)   |          | ENGR BY   |              |
| TOLERANCES:  |          | DRAWN BY  | MAZ          |
| X= ±1  | XX= ±.25 | CHECKED BY  | 29DEC15      |
| .X= ±.5  | ∠= ±1°   | USED ON   |              |
| DIMENSIONING AND TOLERANCING PER ASME Y14.5M-1994  |          | MATERIAL  |              |
| THIRD ANGLE PROJECTION   |          | FINISH  |              |
|  |          |   |              |
| <small>THIS DRAWING CONTAINS INFORMATION PROPRIETARY TO PLANAR SYSTEMS, INC. ANY REPRODUCTION IN PART OR WHOLE WITHOUT THE WRITTEN PERMISSION OF PLANAR SYSTEMS IS PROHIBITED. THIS DRAWING IS SUPPLIED FOR INFORMATION, IDENTIFICATION, ENGINEERING, EVALUATION, AND/OR INSPECTION PURPOSES ONLY AND MAY NOT BE USED AS BASIS FOR THE MANUFACTURING OF PRODUCTS OR THE FURNISHING OF SERVICES TO PLANAR SYSTEMS OR TO ANY THIRD PARTY UNLESS AUTHORIZED IN WRITING BY PLANAR SYSTEMS.</small> |          | <small>PLANAR SYSTEMS, INC.<br/>1195 NW COMPTON DRIVE<br/>BEAVERTON, OR 97006 USA</small> |              |
| TITLE  |          | CLARITY MATRIX MX/LX55HDX-L<br>3X2 MOUNT BRACKET LAYOUT                                   |              |
| SIZE   | PART NO. | DRAWING NO.   | REV          |
| D  | -        | HX2 55L Outline   | A            |
| SCALE  | 1:5      | DO NOT SCALE  | SHEET 3 OF 8 |



4. IT IS RECOMMENDED THAT FOR FLUSH MOUNT WALLS, A MINIMUM OF 13mm (0.5") GAP BE LEFT AT THE SIDES AND A MINIMUM OF 25mm (1.0") GAP BE LEFT AT THE BOTTOM. SEE PAGE ONE FOR TOP GAP RECOMMENDATIONS

3. IT IS RECOMMENDED THAT A MINIMUM OF 5 FEET OF CABLE IS AVAILABLE FOR PANELS NEXT TO THE CONDUIT OPENING. MORE WILL BE NEEDED FOR PANELS FARTHER AWAY.



2. ENSURE THE LCD MOUNTS ARE MOUNTED FLAT, LEVEL, AND PLUMB.

1. SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE


NOTES: UNLESS OTHERWISE SPECIFIED.

|  |          |   |  |
|--|----------|---|--|
| UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN MILLIMETERS (INCHES) |          | ENGR BY   | PLANAR SYSTEMS, INC.<br>1195 NW COMPTON DRIVE<br>BEAVERTON, OR 97006 USA |
| TOLERANCES:  |          | DRAWN BY  | MAZ  |
| X= ±1  | XX= ±.25 | CHECKED BY  | 29DEC15  |
| .X= ±.5  | ∠= ±1°   | USED ON   |  |
| DIMENSIONING AND TOLERANCING PER ASME Y14.5M-1994                  |          | MATERIAL  |  |
| THIRD ANGLE PROJECTION   |          | FINISH  |  |
|  |          | <b>PLANAR</b>   |  |
|  |          | <b>CLARITY MATRIX MX/LX55HDX-L<br/>3X3 MOUNT BRACKET LAYOUT</b> |  |
| SIZE   | PART NO. | DRAWING NO.   | REV  |
| D  | -        | HX2 55L Outline   | A  |
| SCALE  | 1:10     | DO NOT SCALE  | SHEET 4 OF 8   |

THIS DRAWING CONTAINS INFORMATION PROPRIETARY TO PLANAR SYSTEMS, INC. ANY REPRODUCTION IN PART OR WHOLE WITHOUT THE WRITTEN PERMISSION OF PLANAR SYSTEMS IS PROHIBITED. THIS DRAWING IS SUPPLIED FOR INFORMATION, IDENTIFICATION, ENGINEERING, EVALUATION, AND/OR INSPECTION PURPOSES ONLY AND MAY NOT BE USED AS BASIS FOR THE MANUFACTURING OF PRODUCTS OR THE FURNISHING OF SERVICES TO PLANAR SYSTEMS OR TO ANY THIRD PARTY UNLESS AUTHORIZED IN WRITING BY PLANAR SYSTEMS.



**OPTIONAL LANDSCAPE WALL STUD ADAPTER BRACKET**  
2 PER LCD MOUNT, ATTACHMENT ORIENTATION SHOWN



5. WALL DIMENSIONS (mm/in)

| ROWS | COLUMNS | HEIGHT | WIDTH  | DIAGONAL |
|------|---------|--------|--------|----------|
| 2    | 2       | 1370.6 | 53.96  | 2429.0   |
| 2    | 3       | 1370.6 | 53.96  | 3644.7   |
| 3    | 3       | 2057.1 | 80.99  | 3644.7   |
| 3    | 4       | 2057.1 | 80.99  | 4860.3   |
| 4    | 4       | 2743.5 | 108.01 | 4860.3   |
| 5    | 5       | 3430.0 | 135.04 | 6076.0   |

4. IT IS RECOMMENDED THAT FOR FLUSH MOUNT WALLS, A MINIMUM OF 13mm (0.5") GAP BE LEFT AT THE SIDES AND A MINIMUM OF 25mm (1.0") GAP BE LEFT AT THE BOTTOM. SEE PAGE ONE FOR TOP GAP RECOMMENDATIONS

3. IT IS RECOMMENDED THAT A MINIMUM OF 5 FEET OF CABLE IS AVAILABLE FOR PANELS NEXT TO THE CONDUIT OPENING. MORE WILL BE NEEDED FOR PANELS FARTHER AWAY.






2. ENSURE THE LCD MOUNTS ARE MOUNTED FLAT, LEVEL, AND PLUMB.

1. SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE

NOTES: UNLESS OTHERWISE SPECIFIED.

|  |         |              |         |                             |  |
|--|---------|--------------|---------|-----------------------------|--|
| UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN MILLIMETERS (INCHES) |         | ENGR BY      | 29DEC15 | <b>PLANAR</b>               | PLANAR SYSTEMS, INC.<br>1195 NW COMPTON DRIVE<br>BEAVERTON, OR 97008 USA |
| TOLERANCES:  |         | DRAWN BY     | MAZ     |                             |  |
| X= ±1  | XX= ±25 | CHECKED BY   |         | TITLE                       |  |
| X= ±5  | ∠= ±1°  | USED ON      |         | CLARITY MATRIX MX/LX55HDX-L |  |
| DIMENSIONING AND TOLERANCING PER ASME Y14.5M-1994                  |         | MATERIAL     |         | ERO MOUNT BRACKET LAYOUT    |  |
| THIRD ANGLE PROJECTION   |         | FINISH       |         | SIZE                        | DRAWING NO.  |
|  |         |              |         | D                           | HX2 55L Outline  |
| SCALE  | 1:5     | DO NOT SCALE | SHEET   | 5 OF 8                      |  |


THIS DRAWING CONTAINS INFORMATION PROPRIETARY TO PLANAR SYSTEMS, INC. ANY REPRODUCTION IN PART OR WHOLE WITHOUT THE WRITTEN PERMISSION OF PLANAR SYSTEMS IS PROHIBITED. THIS DRAWING IS SUPPLIED FOR INFORMATION, IDENTIFICATION, ENGINEERING, EVALUATION, AND/OR INSPECTION PURPOSES ONLY AND MAY NOT BE USED AS BASIS FOR THE MANUFACTURING OF PRODUCTS OR THE FURNISHING OF SERVICES TO PLANAR SYSTEMS OR TO ANY THIRD PARTY UNLESS AUTHORIZED IN WRITING BY PLANAR SYSTEMS.



- 2. TOP, BOTTOM, LEFT AND RIGHT TRIM ARE 2mm THICK
  - 1. SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE
- NOTES: UNLESS OTHERWISE SPECIFIED.

|   |          |   |       |  |
|---|----------|---|-------|--|
| UNLESS OTHERWISE SPECIFIED:<br>DIMENSIONS ARE IN MILLIMETERS (INCHES) |          | ENGR BY   |       | PLANAR SYSTEMS, INC.<br>1195 NW COMPTON DRIVE<br>BEAVERTON, OR 97006 USA |
| TOLERANCES:   |          | DRAWN BY  | MAZ   | 29DEC15  |
| X= ±1   | XX= ±.25 | CHECKED BY  |       |  |
| .X= ±.5   | ∠= ±1°   | USED ON   |       |  |
| DIMENSIONING AND TOLERANCING PER<br>ASME Y14.5M-1994                  |          | MATERIAL  |       |  |
| THIRD ANGLE PROJECTION  |          | FINISH  |       |  |
|   |          | <b>CLARITY MATRIX MX/LX55HDX-L TRIM INSTALL OPTIONS</b> |       |  |
| SIZE  | PART NO. | DRAWING NO.   | REV   |  |
| D   | -        | HX2 55L Outline   | A     |  |
| SCALE   | 1:5      | DO NOT SCALE  | SHEET | 6 OF 8   |


THIS DRAWING CONTAINS INFORMATION PROPRIETARY TO PLANAR SYSTEMS, INC. ANY REPRODUCTION IN PART OR WHOLE WITHOUT THE WRITTEN PERMISSION OF PLANAR SYSTEMS IS PROHIBITED. THIS DRAWING IS SUPPLIED FOR INFORMATION, IDENTIFICATION, ENGINEERING, EVALUATION, AND/OR INSPECTION PURPOSES ONLY AND MAY NOT BE USED AS BASIS FOR THE MANUFACTURING OF PRODUCTS OR THE FURNISHING OF SERVICES TO PLANAR SYSTEMS OR TO ANY THIRD PARTY UNLESS AUTHORIZED IN WRITING BY PLANAR SYSTEMS.



4. TIE BACKS REQUIRED FOR WALLS EXCEEDING 7 FEET TALL AT THE TOP AND MINIMUM EVERY 7 FEET BEYOND.
  3. STANDARD MAXIMUM THREE HEIGHT STACK. CONTACT PLANAR FOR CUSTOM OPTIONS FOR ADDITIONAL ROWS.
  2. ADDITIONAL CUSTOM ACCESSORIES. CONTACT PLANAR SYSTEMS.
    - CASTERS
    - FLOOR ANCHORING WITHOUT FEET
    - CUSTOM LENGTHS
  1. SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.
- NOTES: UNLESS OTHERWISE SPECIFIED.

|  |          |            |     |         |  |
|--|----------|------------|-----|---------|--|
| UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN MILLIMETERS (INCHES) |          | ENGR BY    |     | PLANAR  | PLANAR SYSTEMS, INC.<br>1195 NW COMPTON DRIVE<br>BEAVERTON, OR 97006 USA |
| TOLERANCES:  |          | DRAWN BY   | MAZ | 29DEC15 |  |
| X= ±1  | XX= ±.25 | CHECKED BY |     |         |  |
| .X= ±.5  | ∠= ±1°   | USED ON    |     |         | TITLE  |
| DIMENSIONING AND TOLERANCING PER ASME Y14.5M-1994                  |          | MATERIAL   |     |         | CLARITY MATRIX MX/LX55HDX-L COLUMN STAND                                 |
| THIRD ANGLE PROJECTION   |          | FINISH     |     |         | SIZE   |
|  |          |            |     |         | D  |
|  |          |            |     |         | PART NO.   |
|  |          |            |     |         | -  |
|  |          |            |     |         | DRAWING NO.  |
|  |          |            |     |         | HX2 55L Outline  |
|  |          |            |     |         | REV  |
|  |          |            |     |         | A  |
|  |          |            |     |         | SCALE  |
|  |          |            |     |         | 1:5  |
|  |          |            |     |         | DO NOT SCALE   |
|  |          |            |     |         | SHEET  |
|  |          |            |     |         | 7 OF 8   |

THIS DRAWING CONTAINS INFORMATION PROPRIETARY TO PLANAR SYSTEMS, INC. ANY REPRODUCTION IN PART OR WHOLE WITHOUT THE WRITTEN PERMISSION OF PLANAR SYSTEMS IS PROHIBITED. THIS DRAWING IS SUPPLIED FOR INFORMATION, IDENTIFICATION, ENGINEERING, EVALUATION, AND/OR INSPECTION PURPOSES ONLY AND MAY NOT BE USED AS BASIS FOR THE MANUFACTURING OF PRODUCTS OR THE FURNISHING OF SERVICES TO PLANAR SYSTEMS OR TO ANY THIRD PARTY UNLESS AUTHORIZED IN WRITING BY PLANAR SYSTEMS.



HANDLES

DO NOT HANDLE THIS AREA

ELECTRONICS INTERFACE

POSITION SENSOR RECEIVER

2X POSITION SENSOR TRANSMITTER

TOP VIEW

STANDARD PANEL DIMENSIONS  
[47.71]  
1211.8

ERO PANEL DIMENSIONS  
[47.73]  
1212.5

ERO PANEL SHOWN

STANDARD PANEL DIMENSIONS  
[26.87]  
682.6

ERO PANEL DIMENSIONS  
[26.90]  
683.3

FRONT VIEW  
STANDARD PANEL

[3.37]  
85.6  
ERO PANEL NOMINAL

[3.29]  
83.5  
STANDARD PANEL NOMINAL

SIDE VIEW

BACK VIEW

4X M6X1.0

[15.75]  
400.0

BOTTOM VIEW

- 2. ROTATE 90° CLOCKWISE AS VIEWED FROM THE FRONT FOR POTRAIT ORIENTATION
  - 1. SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE
- NOTES: UNLESS OTHERWISE SPECIFIED.

|   |          |                             |   |  |
|---|----------|-----------------------------|---|--|
| UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN MILLIMETERS (INCHES) |          | ENGR BY MAZ 30DEC15         |   | PLANAR SYSTEMS, INC.<br>1195 NW COMPTON DRIVE<br>BEAVERTON, OR 97006 USA |
| TOLERANCES:   |          | DRAWN BY MAZ 30DEC15        |   |  |
| X= ±1   | XX= ±.25 | CHECKED BY                  | TITLE   |  |
| .X= ±.5   | ∠= ±1°   | USED ON                     | CLARITY MATRIX MX55HDX-L VESA INSTALL OUTLINE |  |
| DIMENSIONING AND TOLERANCING PER ASME Y14.5M-1994                 |          | MATERIAL                    | SIZE  | PART NO.   |
| THIRD ANGLE PROJECTION  |          | FINISH                      | D   | -  |
|   |          | DRAWING NO. HX2 55L Outline |   |  |
|   |          | SCALE 1:5 DO NOT SCALE      |   |  |
|   |          | SHEET 8 OF 8                |   |  |

THIS DRAWING CONTAINS INFORMATION PROPRIETARY TO PLANAR SYSTEMS, INC. ANY REPRODUCTION IN PART OR WHOLE WITHOUT THE WRITTEN PERMISSION OF PLANAR SYSTEMS IS PROHIBITED. THIS DRAWING IS SUPPLIED FOR INFORMATION, IDENTIFICATION, ENGINEERING, EVALUATION, AND/OR INSPECTION PURPOSES ONLY AND MAY NOT BE USED AS BASIS FOR THE MANUFACTURING OF PRODUCTS OR THE FURNISHING OF SERVICES TO PLANAR SYSTEMS OR TO ANY THIRD PARTY UNLESS AUTHORIZED IN WRITING BY PLANAR SYSTEMS.