






REVISION HISTORY					
ECO	ZONE	REV.	DESCRIPTION	DATE	APPR'D
		01	INITIAL RELEASE	11/29/2018	MTS
		02	ADDED NOTE NUMBER TO WALL SIZE TABLES AND FIXED VESA DIMENSIONS	10/29/2019	MTS
		03	FIXED ERO MOUNT LAYOUT	7/20/2021	MTS

MINIMUM GAP TO CEILING		
CONDITION	mm	in
SERVICE MODE	38	1.5
TOOL ACCESS	165	6.5
PANEL REMOVAL ONLY	32	1.3
MINIMUM GAP	17	0.7



FRONT VIEW
ERO PANEL SHOWN




BOTTOM VIEW

WITHOUT MOUNT
STANDARD PANEL SHOWN




WITH MOUNT
ERO PANEL SHOWN



SIDE VIEWS

SERVICE MODE



- PANEL TEMPERATURES CAN INCREASE 3-5° C WITH EACH VERTICALLY STACKED UNIT.
 - SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.
- NOTES: UNLESS OTHERWISE SPECIFIED.




UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN MILLIMETERS (INCHES)		ENGR BY	24 Sep 18
TOLERANCES:		DRAWN BY	24 Sep 18
X= ±1	XX= ±25	CHECKED BY	24 Sep 18
.X= ±.5	∠= ±1°	USED ON	
DIMENSIONING AND TOLERANCING PER ASME Y14.5M-1994		MATERIAL	
THIRD ANGLE PROJECTION		FINISH	



CLARITY MATRIX MX65U-P
PRODUCT OUTLINE

SIZE	PART NO.	DRAWING NO.	REV.
D	-	-	-
SCALE	1:8	DO NOT SCALE	SHEET 1 OF 6

THIS DRAWING CONTAINS INFORMATION PROPRIETARY TO PLANAR SYSTEMS, INC. ANY REPRODUCTION IN PART OR WHOLE WITHOUT THE WRITTEN PERMISSION OF PLANAR SYSTEMS IS PROHIBITED. THIS DRAWING IS SUPPLIED FOR INFORMATION, IDENTIFICATION, ENGINEERING, EVALUATION, AND/OR INSPECTION PURPOSES ONLY AND MAY NOT BE USED AS BASIS FOR THE MANUFACTURING OF PRODUCTS OR THE FURNISHING OF SERVICES TO PLANAR SYSTEMS OR TO ANY THIRD PARTY UNLESS AUTHORIZED IN WRITING BY PLANAR SYSTEMS.





5. STANDARD WALL DIMENSIONS (mm/in)

ROWS	COLUMNS	HEIGHT	WIDTH	DIAGONAL			
2	2	2867.5	112.90	1617.6	63.69	3292.3	129.62
2	3	2867.5	112.90	2426.6	95.54	3756.5	147.89
3	3	4301.5	169.35	2426.6	95.54	4938.8	194.44
3	4	4301.5	169.35	3235.6	127.39	5382.6	211.91
4	4	5735.4	225.80	3235.6	127.39	6585.2	259.26
5	5	7169.4	282.26	4044.6	159.24	8231.6	324.08

- IT IS RECOMMENDED THAT FOR FLUSH WALLS, A MINIMUM OF 13mm (0.5") GAP BE LEFT AT THE SIDES AND A MINIMUM OF 25mm (1.0") GAP BE LEFT AT THE BOTTOM. SEE PAGE ONE FOR TOP GAP RECOMMENDATIONS.
 - IT IS RECOMMENDED THAT A MINIMUM OF 5 FEET OF CABLE IS AVAILABLE FOR PANELS NEXT TO THE CONDUIT OPENING. MORE WILL BE NEEDED FOR PANELS FARTHER AWAY.
 - ENSURE THE LCD MOUNTS ARE MOUNTED FLAT, LEVEL, AND PLUMB.
 - SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.
- NOTES: UNLESS OTHERWISE SPECIFIED.

UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN MILLIMETERS (INCHES)		ENGR BY	24 Sep 18	PLANAR SYSTEMS, INC. 1195 NE COMPTON DRIVE HILLSBORO, OR 97006 USA
TOLERANCES:		DRAWN BY	24 Sep 18	
X= ±1	XX= ±25	CHECKED BY	24 Sep 18	TITLE
.X= ±.5	∠= ±1°	USED ON		CLARITY MATRIX MX65-P 2x2 MOUNT BRACKET LAYOUT
DIMENSIONING AND TOLERANCING PER ASME Y14.5M-1994		MATERIAL		SIZE
THIRD ANGLE PROJECTION		FINISH		PART NO.
				DRAWING NO.
				REV
				SCALE
				1:8
				DO NOT SCALE
				SHEET
				2 OF 6

THIS DRAWING CONTAINS INFORMATION PROPRIETARY TO PLANAR SYSTEMS, INC. ANY REPRODUCTION IN PART OR WHOLE WITHOUT THE WRITTEN PERMISSION OF PLANAR SYSTEMS IS PROHIBITED. THIS DRAWING IS SUPPLIED FOR INFORMATION, IDENTIFICATION, ENGINEERING, EVALUATION, AND/OR INSPECTION PURPOSES ONLY AND MAY NOT BE USED AS BASIS FOR THE MANUFACTURING OF PRODUCTS OR THE FURNISHING OF SERVICES TO PLANAR SYSTEMS OR TO ANY THIRD PARTY UNLESS AUTHORIZED IN WRITING BY PLANAR SYSTEMS.




5. STANDARD WALL DIMENSIONS (mm/in)

ROWS	COLUMNS	HEIGHT	WIDTH	DIAGONAL
2	2	2869.1	112.96	1619.2
2	3	2869.1	112.96	2429.0
3	3	4303.9	169.44	2429.0
3	4	4303.9	169.44	3238.8
4	4	5738.6	225.93	3238.8
5	5	7173.4	282.42	4048.6

4. IT IS RECOMMENDED THAT FOR FLUSH WALLS, A MINIMUM OF 13mm (0.5") GAP BE LEFT AT THE SIDES AND A MINIMUM OF 25mm (1.0") GAP BE LEFT AT THE BOTTOM. SEE PAGE ONE FOR TOP GAP RECOMMENDATIONS.
3. IT IS RECOMMENDED THAT A MINIMUM OF 5 FEET OF CABLE IS AVAILABLE FOR PANELS NEXT TO THE CONDUIT OPENING. MORE WILL BE NEEDED FOR PANELS FARTHER AWAY.
2. ENSURE THE LCD MOUNTS ARE MOUNTED FLAT, LEVEL, AND PLUMB.
1. SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.
- NOTES: UNLESS OTHERWISE SPECIFIED.


UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN MILLIMETERS (INCHES)		ENGR BY	24 Sep 18	 PLANAR SYSTEMS, INC. 1195 NE COMPTON DRIVE HILLSBORO, OR 97006 USA
TOLERANCES:		DRAWN BY	24 Sep 18	
X= ±1	XX= ±25	CHECKED BY	24 Sep 18	
.X= ±.5	∠= ±1°	USED ON		
DIMENSIONING AND TOLERANCING PER ASME Y14.5M-1994		MATERIAL		
THIRD ANGLE PROJECTION		FINISH		
THIS DRAWING CONTAINS INFORMATION PROPRIETARY TO PLANAR SYSTEMS, INC. ANY REPRODUCTION IN PART OR WHOLE WITHOUT THE WRITTEN PERMISSION OF PLANAR SYSTEMS IS PROHIBITED. THIS DRAWING IS SUPPLIED FOR INFORMATION, IDENTIFICATION, ENGINEERING, EVALUATION, AND/OR INSPECTION PURPOSES ONLY AND MAY NOT BE USED AS BASIS FOR THE MANUFACTURING OF PRODUCTS OR THE FURNISHING OF SERVICES TO PLANAR SYSTEMS OR TO ANY THIRD PARTY UNLESS AUTHORIZED IN WRITING BY PLANAR SYSTEMS.				TITLE CLARITY MATRIX MX65-P ERO 2x2 MOUNT BRACKET LAYOUT
SIZE	PART NO.	DRAWING NO.	REV.	
D	-	-	-	
SCALE	1:8	DO NOT SCALE	SHEET 3 OF 6	



4. IT IS RECOMMENDED THAT FOR FLUSH WALLS, A MINIMUM OF 13mm (0.5") GAP BE LEFT AT THE SIDES AND A MINIMUM OF 25mm (1.0") GAP BE LEFT AT THE BOTTOM. SEE PAGE ONE FOR TOP GAP RECOMMENDATIONS.
 3. IT IS RECOMMENDED THAT A MINIMUM OF 5 FEET OF CABLE IS AVAILABLE FOR PANELS NEXT TO THE CONDUIT OPENING. MORE WILL BE NEEDED FOR PANELS FARTHER AWAY.
 2. ENSURE THE LCD MOUNTS ARE MOUNTED FLAT, LEVEL, AND PLUMB.
 1. SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.
- NOTES: UNLESS OTHERWISE SPECIFIED.

UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN MILLIMETERS (INCHES)		ENGR BY	24 Sep 18	 <small>PLANAR SYSTEMS, INC. 1195 NE COMPTON DRIVE HILLSBORO, OR 97006 USA</small>
TOLERANCES:		DRAWN BY	24 Sep 18	
X= ±1	XX= ±.25	CHECKED BY	24 Sep 18	TITLE
.X= ±.5	∠= ±1°	USED ON		CLARITY MATRIX MX65-P 3x2 MOUNT BRACKET LAYOUT
DIMENSIONING AND TOLERANCING PER ASME Y14.5M-1994		MATERIAL		SIZE
THIRD ANGLE PROJECTION		FINISH		D
				PART NO.
				-
				DRAWING NO.
				-
				REV
SCALE	1:8	DO NOT SCALE	SHEET	4 OF 6

THIS DRAWING CONTAINS INFORMATION PROPRIETARY TO PLANAR SYSTEMS, INC. ANY REPRODUCTION IN PART OR WHOLE WITHOUT THE WRITTEN PERMISSION OF PLANAR SYSTEMS IS PROHIBITED. THIS DRAWING IS SUPPLIED FOR INFORMATION, IDENTIFICATION, ENGINEERING, EVALUATION, AND/OR INSPECTION PURPOSES ONLY AND MAY NOT BE USED AS BASIS FOR THE MANUFACTURING OF PRODUCTS OR THE FURNISHING OF SERVICES TO PLANAR SYSTEMS OR TO ANY THIRD PARTY UNLESS AUTHORIZED IN WRITING BY PLANAR SYSTEMS.



DISPLAY OUTLINE


RECOMMENDED LOCATION FOR CABLE INGRESS BETWEEN PANEL COLUMNS

4. IT IS RECOMMENDED THAT FOR FLUSH WALLS, A MINIMUM OF 13mm (0.5") GAP BE LEFT AT THE SIDES AND A MINIMUM OF 25mm (1.0") GAP BE LEFT AT THE BOTTOM. SEE PAGE ONE FOR TOP GAP RECOMMENDATIONS.
 3. IT IS RECOMMENDED THAT A MINIMUM OF 5 FEET OF CABLE IS AVAILABLE FOR PANELS NEXT TO THE CONDUIT OPENING. MORE WILL BE NEEDED FOR PANELS FARTHER AWAY.
 2. ENSURE THE LCD MOUNTS ARE MOUNTED FLAT, LEVEL, AND PLUMB.
 1. SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.
- NOTES: UNLESS OTHERWISE SPECIFIED.



UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN MILLIMETERS (INCHES)		ENGR BY	24 Sep 18		PLANAR SYSTEMS, INC. 1195 NE COMPTON DRIVE HILLSBORO, OR 97006 USA
TOLERANCES:		DRAWN BY	24 Sep 18		
X= ±1	XX= ±.25	CHECKED BY	24 Sep 18	TITLE	
.X= ±.5	∠= ±1°	USED ON		CLARITY MATRIX MX65-P 3x3 MOUNT BRACKET LAYOUT	
DIMENSIONING AND TOLERANCING PER ASME Y14.5M-1994		MATERIAL		SIZE	PART NO.
THIRD ANGLE PROJECTION		FINISH		DRAWING NO.	REV
				D	-
<small>THIS DRAWING CONTAINS INFORMATION PROPRIETARY TO PLANAR SYSTEMS, INC. ANY REPRODUCTION IN PART OR WHOLE WITHOUT THE WRITTEN PERMISSION OF PLANAR SYSTEMS IS PROHIBITED. THIS DRAWING IS SUPPLIED FOR INFORMATION, IDENTIFICATION, ENGINEERING, EVALUATION, AND/OR INSPECTION PURPOSES ONLY AND MAY NOT BE USED AS BASIS FOR THE MANUFACTURING OF PRODUCTS OR THE FURNISHING OF SERVICES TO PLANAR SYSTEMS OR TO ANY THIRD PARTY UNLESS AUTHORIZED IN WRITING BY PLANAR SYSTEMS.</small>		SCALE	1:12	DO NOT SCALE	SHEET 5 OF 6

8 7 6 5 4 3 2 1



TRIM INSTALLATION




TOP TRIM




BOTTOM TRIM



LEFT TRIM



RIGHT TRIM



- 2. TOP, BOTTOM, LEFT, AND RIGHT TRIM ARE 2mm THICK
 - 1. SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.
- NOTES: UNLESS OTHERWISE SPECIFIED.

UNLESS OTHERWISE SPECIFIED: DIMENSIONS ARE IN MILLIMETERS (INCHES)		ENGR BY 24 Sep 18	DRAWING NO.	
TOLERANCES:		DRAWN BY 24 Sep 18	PART NO.	
X= ±1	XX= ±25	CHECKED BY 24 Sep 18	DRAWING NO.	
.X= ±.5	∠= ±1°	USED ON	REV	
DIMENSIONING AND TOLERANCING PER ASME Y14.5M-1994		MATERIAL	TITLE	
THIRD ANGLE PROJECTION		FINISH	CLARITY MATRIX MX65-P TRIM INSTALL OPTIONS	
		SIZE: D SCALE: 1:8 DO NOT SCALE SHEET: 6 OF 6		

THIS DRAWING CONTAINS INFORMATION PROPRIETARY TO PLANAR SYSTEMS, INC. ANY REPRODUCTION IN PART OR WHOLE WITHOUT THE WRITTEN PERMISSION OF PLANAR SYSTEMS IS PROHIBITED. THIS DRAWING IS SUPPLIED FOR INFORMATION, IDENTIFICATION, ENGINEERING, EVALUATION, AND/OR INSPECTION PURPOSES ONLY AND MAY NOT BE USED AS BASIS FOR THE MANUFACTURING OF PRODUCTS OR THE FURNISHING OF SERVICES TO PLANAR SYSTEMS OR TO ANY THIRD PARTY UNLESS AUTHORIZED IN WRITING BY PLANAR SYSTEMS.

8 7 6 5 4 3 2 1